



Symbol	Millimeters			Inches		
	Min.	Nom.	Max.	Min.	Nom.	Max.
A	0.535 REF.			.021 REF.		
B	2.39	2.54	2.69	.094	.100	.106
C	0.436	0.510	0.711	.017	.020	.028
D	2.19	2.34	2.49	.086	.092	.098
E	1.91	2.16	2.41	.075	.085	.095
F	1.32	1.52	1.72	.052	.060	.068
G	.010	.015	0.20	.004	.006	.008
H	0.535	0.660	0.785	.021	.026	.031
J	0.05	0.10	0.15	.002	.004	.006
K	0.65	0.75	0.85	.025	.029	.033
L	0.85	0.95	1.05	.033	.037	.041
M	4.53	4.68	4.83	.178	.184	.190
N	4.73	4.88	5.03	.0186	.192	.198

Notes:

1. Tin plating thickness: 7.5-20.5 μm

UNLESS OTHERWISE SPECIFIED:

ALL DIMENSIONS ARE IN mm (in)

TOLERANCES:

DECIMALS ANGLES

X.X ± 0.1 ± 1.0°

X.XX ± 0.05

X.XXX ± 0.010

INTERPRET GEOMETRIC TOLERANCING PER:

MATERIAL:

FINISH:

DO NOT SCALE DRAWING

DRAWN NAME DATE

CHECKED DRK

ENG APPR.

MPG APPR.

G.A.

COMMENTS:

Akoustis, Inc.
9805-H Northcross Center Court
Huntersville, NC 28078

TITLE: Plastic Micro-X
with Matte-Tin Leads

SIZE DWG. NO. REV
B AKA-00103 0

SCALE: 20:1 WEIGHT: SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AKOUSTIS TECHNOLOGIES, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AKOUSTIS TECHNOLOGIES, INC IS PROHIBITED.