


SF2592NM

897.5/942.5 MHz Filter Duplexer



SM1814

MAXIMUM RATING:

- Operating temperature range: -30 °C to +85 °C
- Storage temperature range: -30 °C to +85 °C
- Input power : 29dB (Ta=+50°C,10000h,WCDMA modulation)
- Maximum DC Voltage: +/-3 V
- Moisture Sensitivity Level: Level 1 (MSL 1)
- ESD 100V(MM) 200V(HBM)

ELECTRICAL CHARACTERISTICS:

Terminating impedance (Tx Port): 50 Ω (Single-ended)

Terminating impedance (Rx Port): 100 Ω (Differential)

Terminating impedance (Ant Port): 50//7.5nH Ω (Q=∞) (Single-ended)

Tx to ANT (f_{T0}=897.5 MHz)

Parameters Description		Unit	Min	Typ	Max	Remarks
Insertion Loss	882.4~912.6MHz	dB(*1)	-	1.5	2.4(*2)	
	880~915MHz	dB(*1)		1.9	3.4	
Amplitude ripple	882.4~912.6MHz	dB	-	0.6	1.9	
	880~915MHz	v		1.0	2.9	
VSWR	ANT		-	-	2.0	2.6
	Tx		-	-	1.8	2.4
Attenuation:						
927.4~957.6 MHz		dB	42(*2)	47	-	
1573.3~1605.9 MHz		dB	40	45	-	
1760~1830 MHz		dB	40	45	-	
2640~2745 MHz		dB	25	32	-	



CAUTION: Electrostatic Sensitive Device. Observe precautions for handling.

NOTES:

1. The design, manufacturing process, and specifications of this device are subject to change.
2. US or International patents may apply.
3. RoHS compliant from the first date of manufacture.

ANT to Rx ($f_{T0}=942.5$ MHz)


Parameters Description		Unit	Min	Typ	Max	Remarks
Insertion Loss	927.4~957.6 MHz	dB(*1)	-	1.9	2.4(*2)	
	925~960 MHz	dB(*1)		2.1	3.1	
Amplitude ripple	927.4~957.6 MHz	dB	-	0.7	1.6	
	925~960 MHz	dB		0.9	2.3	
Amplitude balance	925~960 MHz	dB	-0.7	-0.1/+0.3	+0.7	
Phase balance	925~960 MHz	dB	-7	-1/+3	+7	
VSWR	ANT		-	1.9	2.3	
	Rx		-	2.0	2.4	
Attenuation:						
882.4~912.6 MHz		dB	48 (*2)	54	-	
2400~2500 MHz		dB	40	49	-	

Tx to Rx

Isolation	882.4~912.6MHz	dB	52(*2)	56	-	
	927.4~957.6 MHz	dB	47 (*2)	51	-	


(*1) Specification of insertion loss excludes loss that comes from the test board.

(*2) Integrated over +/-1.92MHz around the WCDMA channel center frequency


Evaluation Circuit**Figure 2. Evaluation Circuit**

FREQUENCY CHARACTERISTICS:

Tx to Ant




Ant to Rx




These data **exclude** loss that comes from the test board.

Tx to Ant ,Ant to Rx





Tx to Rx Isolation





These data **exclude** loss that comes from the test board



Tx Port




Rx Port




Ant Port




Ant to Rx (Amplitude balance)




Ant to Rx (Phase balance)




Tx to Ant (Wide span)



Ant to Rx (Wide span)



**OUTLINE DRAWING:
(Mass Production)**



Marking name : SCF

△: Date code(2016 May → s ,....., 2019 Dec→m.)

◇◇: Lot Code.

Product Date Code. Follow below table.


Year	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
2016	n	p	q	r	s	t	u	v	w	x	y	z
2017	A	B	C	D	E	F	G	H	J	K	L	M
2018	N	P	Q	R	S	T	U	V	W	X	Y	Z
2019	a	b	c	d	e	f	g	h	j	k	l	m

Pin Configuration


Pin No.	Pin name	Description
1	Rx	Receiver Pin (balanced)
2	GND	Ground Pin
3	Tx	Transmitter Pin
4	GND	Ground Pin
5	GND	Ground Pin
6	ANT	Antenna Pin
7	GND	Ground Pin
8	Rx	Receiver Pin (balanced)

Figure 1. Dimensions and Pin assignment

Top View (Sample Production):



FOOTPRINT:




PACKING:**REEL DIMENSION**

Reel Count"

7" = 3000

13" = 10,000

**Materials of Reel**

Material : Polystyrene + Carbon


Characteristics : Conforms to EIAJ-ET-7200A

Color : Black

Surface resistance (reference value) : $10^9 \Omega/\text{sq}$ Max.

Unit : mm

Code	Quantity	A	B	C	W1	W2
Z	3,000 pcs	$\phi 180.0 +0.0/-1.5$	$\phi 66.0 +/-.0.5$	$\phi 13.0 +/-.0.2$	$9.0 +1.0/-0.0$	$11.4 +/-.1.0$

TAPE DIMENSION

RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 245~260°C peak (min. 10sec).
4. Time : 2 times.

